

HF /NFC FABRIC WRISTBAND

@RFID offers a wide range of RFID transponders. The **NFC Fabric Wristbands** integrates a copper (CU) wired antenna with bonded RFID chip, laminated between four PVC layers for a total thickness of 0.8mm for the Tag. It is then assembled with a high quality fabric and adjustable closing part, optionally for single or a multiple use.

Full 4x4 colours offset print for the Tag and one colour screen print personalization is available, as well as different fabric band colours.

Applications for HF/NFC RFID Fabric Wristband:

Access Control for:

All-Inclusive Guests

Arena Season Ticket Holders

Authorized Visitors

Club Members

Conference Attendees


Event Participants

VIPs

Your idea/application







Chips:

ISO/IEC 14443:

NXP Mifare Series / NTAG Series @RFID Compatible Series

ISO/IEC 15693: NXP I-Code Series

Technical:

Physical Features:

Material: PVC + Fabric

Working temperature: -20°C ÷ 40°C

Durability: 3-5 years

RFID Features:

Frequency: 13.56MHz Read-Write

Read range: ISO14443A ≥1cm / ISO15693≥5cm

Other Features:

Environmental: ROHS compliant Customization: printable, pre-coded

One shot or multiple use

@RFID Deutschland

udoege@arfid.eu Tel: +49 (0)6074 86 19 30

Fax: +49 (0)3212 8619290



arfidex GmbH Adlerstr. 2 63327 Rödermark

@RFID Headquarters

Mladost 1, No.20/26 1750 Sofia, Bulgaria www.arfid.eu sofia@arfid.eu Tel.: +359 2 888 87 32 54 Fax: + 359 2 884 55 82 VAT: BG 175 33 66 55