






arfiMove
BLUEBERRY HS-UHF
865...868 MHz UHF
KEY-CHAIN
Bluetooth® CLASS 2 V2.1 + EDR
RFID Reader
ISO18000-6

Product:	Mobile KEY-CHAIN STYLE 865-868 MHz UHF RFID Reader Writer with integrated antenna and Bluetooth™ interface to connect with Android™, IOS™, macOS™, Linux or Microsoft Windows™ operating system based smartphone, PC or tablet PC.	
RFID TAGs supported:	ISO18000-6 TAG series Read Write	
Read Range:	up to 2 cm with near field UHF TAG up to 30 cm in free air (Depends on RFID TAG type and shape)	Working time: 7 h continuous reading* 10000 readings, 14 h in idle mode
Frequency*:	865.6 – 867.6 MHz	* = At room temperature 20°C
ISO / Standards:	ISO18000-6	
Material / IP Rate:	Plastic	IP54
Dimensions / Weight:	(68 x 42 x 18) mm	ca. 30 g
Interfaces:	Micro-USB type B, Bluetooth 2 V2.1 Transmission Distance: up to 5 m (in open environment)	HID Human device interface (keyboard emulation) SPP (bidirectional serial) profiles
Power Supply:	Micro USB 380mA peak @ 5VDC (RF full power), 30mA @ 5VDC (idle mode)	Li-Poly Battery 3.7VDC, 300 mAh
Switch:	1 function key for RFID READ activation	
Display / Sound:	2 x LED indicators (power on, BT connection, working status)	Multi-tone Beeper
Temperature:	Operating: -20°C ... + 60°C	Storage: -20°C ... + 60°C
Certification:	 ETSI EN 302 208-2 V1.4.1 ETSI EN300328 V1.8.1	  Made in EUROPE
Part Description:	arfiMove BLUEBERRY HS-UHF	Part-No. 123457020

arfidex GmbH | Adlerstraße 2 | D-63322 Rödermark | Germany | Phone: +49 (0) 6074 861930

www.arfidex.de | info@arfidex.de

© arfidex makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does arfidex assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by arfidex have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by arfidex. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by arfidex hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. arfidex does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to arfidex, and arfidex reserves the right to make any changes to the information in this document or to any products and services at any time without notice.



arfiMove
BLUEBERRY HS-UHF
865...868 MHz UHF
KEY-CHAIN
Bluetooth® CLASS 2 V2.1 + EDR
RFID Reader
ISO18000-6

arfiMove BlueBerry HS UHF is a mobile mini RFID reader, shaped like a keychain, capable of reading HF tags and transmitting the acquired data to any device equipped with a Bluetooth® radio interface.

The reading distance is about 2cm up to 30cm.

The use of the RFID reader is easy and intuitive, thanks to the presence of a single button to activate the reading of the UHF tags, combined with an LED and a multi-tone beeper, to alert the operator of the reading.

arfiMove BlueBerry HS UHF integrates Bluetooth® radio technology, specifically it uses HID and SPP profiles. With the HID profile the data transmission takes place in keyboard emulation mode, mono-directional channel. This profile supports all major mobile devices, including those equipped with the iOS and Android operating systems. It also supports the main desktop and portable devices, including those with Windows, Linux and macOS operating systems.

Thanks to this profile, any application or program that accepts identification data entered from the keyboard can receive the same data transmitted by the arfiMove BlueBerry HS HF. With the SPP profile, data transmission takes place in virtual serial mode, a two-way channel.

A simple serial communication protocol allows the user to manage all the RFID reader functions, in particular, the ID scan and the reading/writing of the UHF tag memory. With this profile, it is also possible, in the development phase, to integrate RFID technology in any application or program for mobile, desktop or laptops.

arfiMove BlueBerry HS UHF is battery powered. Charging is carried out via a micro USB connector.

Through the USB port it is possible to connect the arfiMove BlueBerry HS UHF to a PC, so that it can also be used as a normal RFID desktop reader. Data transmission on the USB interface takes place in virtual serial mode, a bidirectional channel (managed through the same serial communication protocol as the Bluetooth SPP interface) .

arfidex GmbH | Adlerstraße 2 | D-63322 Rödermark | Germany | Phone: +49 (0) 6074 861930

www.arfidex.de | info@arfidex.de

© arfidex makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does arfidex assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by arfidex have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by arfidex. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by arfidex hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. arfidex does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to arfidex, and arfidex reserves the right to make any changes to the information in this document or to any products and services at any time without notice.



arfiMove
BLUEBERRY HS-UHF
865...868 MHz UHF
KEY-CHAIN
Bluetooth® CLASS 2 V2.1 + EDR
RFID Reader
ISO18000-6

This UHF KEYCHAIN RFID reader is used by system integrators/companies to read and write UHF RFID tags, and to send the data in real time to a smartphone, tablet, PDA, PC by using Bluetooth™ wireless technology.

Apps, APIs and SDKs are available for Android™ iOS™ macOS™ Linux and Microsoft Windows™ based devices.

Applications:

- ◆ Industrial ID
- ◆ Inventory (Asset Management)
- Logistics
- ◆ Maintenance, Service, Inspection
- ◆ Waste Management

Options:

The device is also available with other antenna for single reading (small or big) UHF or NFC/HF TAGs in on-metal environment or as desktop version. Other versions for long range UHF TAG reading are also available.



arfidex GmbH | Adlerstraße 2 | D-63322 Rödermark | Germany | Phone: +49 (0) 6074 861930

www.arfidex.de | info@arfidex.de

© arfidex makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does arfidex assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by arfidex have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by arfidex. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by arfidex hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. arfidex does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to arfidex, and arfidex reserves the right to make any changes to the information in this document or to any products and services at any time without notice.