

HF/NFC RFID LABEL /STICKER 20 / 25 / 30 mm

@RFID offers a wide range of RFID transponders.

The **HF NFC RFID LABEL** integrate a PET DRY HF INLAY produced with a cutting edge flip chip machine.

The assembly is done by automatic machinery and high quality adhesive and a high quality PVC surface layer.

The label was developed by the @RFID R&D team based on the advanced know-how and the long term experience. Standard Ø = 20, 25, 30 mm x 0,5 mm

OPTIONS:

- Anti-Metal Function by using additional ferrite foil
- Logo Print and Chip encoding is available.

Applications for HF/NFC RFID LABEL:

- Anti-Counterfeiting
- Assorting
- Clothes
- Garment
- Goods Marking, Pricing
- Inventory made easy
- Logistics Improvement
- NFC Operation / Setting
- Supply Chain Management



Frequencies/Chips:

HF/NFC: ISO 14443A NXP Mifare-/NTAG-/@RFID-compatible Series : 13,56MHz

ISO 15693 NXP I-Code Series

Technical:

Material:	PVC, Adhesive
Operating Temperature:	-20° ... +70°C
Read Range:	ISO14443 ≤ 10 mm ISO15693 ≤ 50 mm (Depends on reader etc.)
Frequencies:	HF 12,5 ... 14 MHz
Antenna:	Copper etched, Ø 10 mm
Environmental:	RoHS compliant
Customized:	Anti-Metal Version, Pre-Encoded Your Logo Print

@RFID Deutschland

udoege@arfid.eu
Tel: +49 (0)6074 86 1930
Fax: +49 (0)3212 8619290
www.arfid.eu



arfidex GmbH www.arfidex.de
Adlerstraße 2
63322 Rödermark
VAT: DE 311 20 55 73

@RFID Headquarters

sofia@arfid.eu
Tel.: +359 2 888 87 32 54
Fax: + 359 2 884 55 82
VAT: BG 175 33 66 55

arfid Ltd
Mladost 1, No.20/26
1750 Sofia, Bulgaria
www.arfid.eu